



**SOLARA**



**Engineered for maximum heating capacity  
in extremely cold climates**

# SOLARA

## PERFORMANCE SPECIFICATIONS



### Heater System Dimensions

42" x 33.3" x 18.6"  
(1,067 x 845 x 459 mm)

### Body Opening

37" x 27.9"  
(940 x 708 mm)

### Approximate Weight

450 lb (200kg)  
Battery: 50 lb (23kg)  
Remote 50-gallon aluminum fuel tank  
with mounting brackets: 65 lb (29 kg)

### Heating Capacity

Ambient at 0°F (-18°C)  
50,000 BTU/hr (14,660 Watts)

### Airflow

Applied System Performance 3,500 cfm  
(5,950 m<sup>3</sup>/hr)

The **Solara™** heating unit is engineered for transporting temperature sensitive products in the coldest of conditions. Designed for trailer and rail applications, the Solara heating unit protects cargo transported in extreme low ambient climates by maintaining temperatures above a specified minimum setpoint.

**Maximum performance.** 50,000 BTU/hr (14,660 W) of heating capacity and 3,500 CFM (5,950m<sup>3</sup>/hr) of airflow allow for premium cargo protection in today's longer, thin-walled trailers, even with multiple door openings.

**APX™ Control System.** The modular APX system combines remarkable control intelligence, temperature control and system reliability with amazingly simple operation.

**Low cost maintenance and service accessibility** through strategic up-front placement of serviceable components and a convenient swing-open, lift-off front door.

### Standard Features Include:

- Tier 4 Final Z482 diesel engine
- 2 cylinder 0.48 liter indirect-injection
- 9.7 HP (7.2kW) at 2,600 RPM speed
- 5.8 qt. (5.4 liter) oil capacity
- High power 70 amp alternator
- Ultra-thin evaporator
- Service interval package
  - Synthetic media oil filter
  - Water-separating heated fuel filter
  - Heavy duty, low noise dry air cleaner
  - Extended-life coolant
- Automatic start/stop fuel saver
- APX™ Control System
  - IntelliSet™
  - DataLink2™ data recorder
  - Information dashboard
  - Multilingual graphical display
  - Pretrip and Virtual Tech diagnostics
  - Integrated USB port
- Single latch release door
- Installation package
- Screw post battery terminals
- Remote aluminum fuel tank
  - 50 gal. single fill – 22"
- Full bottom panel
- Fuel heater

### Accessories and Options:

- DataTrak™ remote communications
- APX flush mount remote control panel
- Remote light bar
- Door Switch
- Remote temperature probe
- Fuel tank level and shutdown sensor
- Exhaust cap
- Flush mount extension kit with access panels
- Remote aluminum fuel tanks:
  - 30 gal. or 75 gal. single fill – 22"
  - 100 gal. single or double fill – 22"
  - 120 gal. single or double fill – 22"
- Anti-siphon fuel cap single or double fill
- Lynx Fleet™ telematics platform

**APX™**  
CONTROL SYSTEM

Specifications are subject to change without notice.

Warranty: Product warranty and limitations are outlined in Form 62-02481.

This warranty applicable only in North America. Consult your Carrier Transcold representative for warranty coverage elsewhere. Form 62-11876 Rev C.

#### North America

Carrier Transcold  
700 Olympic Drive  
Athens, GA 30601 USA

#### Central America and Mexico

Carrier Transcold  
Ejercito Nacional 253-A Piso 5  
Colonia Anahuac  
11320 Mexico D.F.

©2022 Carrier. All Rights Reserved. Printed in USA 7/22.

Carrier, Transcold and Solara are registered trademarks of Carrier Corporation.

**Carrier**  
**TRANSCOLD**

www.trucktrailer.carrier.com